Review Article

An Overview of Studies and Research on Waste **Heat Recovery with Emphasis on Hot Gases**

Sunil J. Kulkarni

Datta Meghe College of Engineering, Airoli, Navi Mumbai, Maharashtra, India.

Received: 04/08/2016 Revised: 22/08/2016 Accepted: 22/08/2016

ABSTRACT

Efficient use of energy resources is one of the most sought after area of studies and research among energy and environment fields. The natural resources of fuel are depleting day by day. The use of renewable resources is considered as promising option. The recovery of waste heat from different thermal units such as boilers, internal combustion units, air conditioners etc. can save considerable amount of energy. Also it reduces thermal pollution. Various investigators have carried out investigation on the use of various waste heat recovery methods. Current review summarizes research and studies on regeneration and recovery of waste heat.

Key words: heat pumps exhaust gases, heat pipes, Rankine cycle, and combustion engines.

INTRODUCTION

Waste heat recovery is one of the solutions for increasing energy demand. The growth of the country, both economical and social, depends on the amount of energy consumed available. and In developing countries, energy availability is becoming problem. The emission of flue gases after combustion is also nuisance to the ecology and environment. [1-3] The gases like hydrogen sulphide, carbon dioxide and oxides of nitrogen can be controlled by various physical, chemical and biological methods. [4-6] The nonconventional energy sources like solar energy, tidal energy, and wind energy are being explored. ^[7,8] The use of pinch technology, fuel cells and heat regeneration are attractive methods for reducing energy consumption. [9,10] The gases from boilers. combustion engines, air conditioners etc. causes thermal pollution. These hot gases can be passed through heat exchangers for recovering their heat. Various investigators have carried out studies and research on

direct and indirect use of energy from hot flue gases. The current review summarizes research and studies on waste heat recovery from hot gases.

E-ISSN: 2349-9788; P-ISSN: 2454-2237

AN OVERVIEW OF STUDIES AND RESEARCH ON WASTE **HEAT** RECOVERY FROM HOT GASES

Jotanovia et al. carried out an investigation on heat recovery in the process of soda ash formation. [11] They used high temperature heat pump in their experiments. A review was carried out by Noor et al. on waste heat recovery technologies in turbocharged automotive engine. [12] They analyzed each process to assess each waste heat recovery technology based on current developments, research trends and its future in an automotive application. According to waste heat from internal them the combustion be utilized engines can thermally, mechanically or electrically and it can be turned into useful form of energy. If adopted by the automotive manufacturers, these green technologies can reduce energy

consumption and global warming. Saadatfdar et al. carried out review on organic Rankine cycle (ORC) for waste heat recovery. [13] They presented an analysis of physical and chemical properties of fluids applications different of ORC. Vijayraghavan and Shriram carried out studies on heat recovery and cogeneration. They emphasized that a lot of energy can be saved by using the waste heat by coupling the heat power plant or boiler to a gas turbine-generator. They tested a two phase cooling system for a waste heat recovery system. They concluded that the power output may be increased and a surplus amount of work can be produced by the heat recovery. Stalin et al. carried out an investigation on use of heat from air conditioner for production of hot water and reduction of LPG gas. [15] According to these studies, if the heat from the air conditioner is used for hot water generation and other LPG applications, minimum 4 cynlider LPG per year can be saved. By using this simple initiative, it is possible to reduce the thermal pollution. Gamma type Stirling engine was applied for heat recovery by Dadi et.al. [16] According to them, it is one of the most efficient methods to recover waste heat. They discussed advantages of Stirling engine. The thermal efficiency of this cycle is equal to Carnot cycle. Also the reasonable amount of work is obtained by this cycle at low swept volume and low pressure. In Gamma type Stirling engine, is connected to the same flywheel but the power piston mounted in a separate cylinder alongside the displacer piston cylinder. Dubey et al. carried out a review on waste heat recovery system. [17] According to their review, the research on waste heat recovery is focused on utilization of heat pipes, Rankine cycle and heat pumps. Low grade thermal sources, with Rankine cycles offer significant potential energy productivity. Heat technology can be applied for upgrading the ambient heat from sustainable sources. Saidur et al. studied methods to recover exhaust heat from internal combustion

[18] engines. They identified potential devices which can be incorporated to have maximum energy recovery. efficiency and net power can be improved by maximizing the potential energy of exhaust gases. Job et al. carried out an investigation on the use of waste heat in an oxy-combustion power plant. [19] They carried out thermodynamic analysis for different cases of compression installations organization. They identified potential for reducing energy consumption compression process. For this purpose, they studied heat recovered in cooling and condensation in the individual processes. This energy can replace lowpressure regeneration. Computational fluid dynamics (CFD) modeling of regenerative heat exchanger was studied by Kic and Zajicek. [20] They carried out studies on heat exchangers suitable for animal houses. The heat generated by presence of animals necessitates proper ventilation. The energy recovery approach can be recuperative and regenerative. The presence of the high dust concentration presents difficulty operation of regeneration equipments and heat exchangers. They used fluent software for airflow and heat exchange simulations. The factors such as thickness of plate, air stream temperature, heating/cooling period or material properties need to be optimized for efficient waste heat recovery.

Albert carried out studies on heat recovery in aluminum cast house. According to him solid aluminum can work as an energy bank. They identified cooling water section as the one with maximum for waste energy recovery possibilities. Flue gases from furnace had maximum energy generation potential. Jadhao and Thombare carried out an investigation on internal combustion gases for recovery potential. [22] According to them only 30 to 40 percent heats is actually converted into useful work. Remaining heat is lost to environment, which may lead to increase in entropy and pollution. The recovery of heat from I.C. engines thus not only reduces pollution but also maximizes

energy efficiency. Sajan et al. carried out investigation on flue gas heat recovery for air conditioning. [23] They placed multipass heat exchanger between the space between boiler and chimney. They used the extracted energy in vapour absorption refrigeration system. The corrosive nature of flue gases limited the recovery to the acid dew point temperature of the flue gas. Mikielewicz carried out an investigation on organic Rankine cycle (ORC) recovery of waste flue gases from coal fired power plant for heat recovery. [24] Initially they supplied the ORC evaporator with hot water at 80 °C. According to these studies, the upper temperature of ORC can be increased by incorporation of absorption heat pumps or solar collectors in the cycle. Srinivasa et al. carried out an investigation on use of electro turbo generation for energy recovery. [25] They explored various heat recovery possibilities in two wheelers and four wheelers. The waste heat energy can be used to burn additional amount of energy. In thermoelectric the second stage the generator was used to utilize waste energy. Compressor and alternator were used in a third stage recovery.

CONCLUSION

The need of clean energy is increasing day by day. The combustion gases and many other gases from process industries many times carry considerable amount of energy and are at high temperature. On one hand, it causes thermal pollution and on the other hand lot of energy is wasted. The extraction of the heat from these gases serves twin purpose of energy and environment. The selection of proper equipment and material for heat transfer is major factor in waste heat recovery from gases.

REFERENCES

 Arvind K. Jha , C. Sharma , Nahar Singh , R. Ramesh, R. Purvaja, Prabhat K. Gupta, "Greenhouse gas emissions from municipal solid waste management in Indian megacities: A case study of Chennai landfill sites", Chemosphere , 2007,doi:10.1016/j.

- chemosphere . 2007.10.024.
- Borjesson G., Svensson, B.H., "Effect of Gas Extraction Interruption on Emissions of CH₄ and CO₂ from a Landfill, and on Methane Oxidation in the Cover Soil", Journal of Environmental Quality, 1997, 26, 1182-1190.
- 3. Onk H., "Dutch Abiogenic Emissions of Methane and Nitrous Oxide and Options for Emission Reduction, Energy Conversion Management, 1996, 37 (6-8), 985-989.
- 4. Sunil Jayant Kulkarni, Ajaygiri Kamalgiri Goswami, "Adsorption for Waste Gas Treatment: A Short Review". IJRASET. 2014, 2(12), 514-515.
- 5. Tanmay Uttam Gound, Veena Ramachandran, Sunil Kulkarni, "Various Methods to Reduce SO₂ Emission- a Review", International Journal of Ethics in Engineering and Management Education, 2014, 1(1), 1-6.
- Veena Ramachandran, Tanmay Uttam Gound, Sunil Kulkarni, "Biofilteration for Waste Gas Treatment-a Review", International Journal of Ethics in Engineering and Management Education, 2014, 1(2), 8-13.
- 7. Sunil Jayant Kulkarni, "Tidal Energy: A Review", International Journal of Research (IJR), 2015, 2(1), 55-58.
- 8. Sunil Jayant Kulkarni, "Solar Distillation: A Review", International Journal of Research (IJR), 2014, 1(11), 1171-1176
- 9. Sunil J. Kulkarni, "A Review on Studies and Research on Fuel Cells", International Journal of Research and Review, 2016, 3(1), 77-80.
- Deepa Ravishankar, "Reducing Hot and Cold Utility Requirements for Finishing Column Section Using Pinch Analysis Techniques", International Journal of Engineering Research and Applications, 2013, 2(4), 1587-1592.
- 11. Milovan Jotanovia, 1Goran Tadia, Vladan Miaia, Darko Gorieanec, "Recovery of Heat from the Waste Flow Formed in the Process of Soda-Ash Production Using a High Temperature Heat Pump", International Journal of Latest Research in Science and Technology, 2014, 3(2), 34-42
- 12. Alias Mohd Noor, Rosnizam Che, Puteh B And Srithar Rajoo, "Waste Heat Recovery Technologies in Turbocharged Automotive Engine- a Review", Journal of Modern Science and Technology, 2014, 2(1), 108-119.
- 13. Behram Saadaftar, Reza Fakrai, Torsten Franson, "Waste Heat Recovery Organic Rankine Cycles In Sustainable Energy Conversion A State-Of-The-Art Review",

- The Journal of Macro Trends In Energy And Sustainability, 2013,1(1),161-188.
- 14. R. Vijayraghvan, S.B. Shreeram, "An Efficient Approach for Heat Recovery and Cogeneration", International Journal of Advanced Electrical and Electronics Engineering, 2013, 2(4), 125-130.
- 15. M. Joseph Stalin, S. Mathana Krishnan, G. Vinoth Kumar, "Efficient Usage of Waste Heat From Air Conditioner", International Journal Of Advances In Engineering and Technology, 2012, 4 (1), 414-423.
- 16. Mohsin J Dadi, Bimran M Molvi, prof. Alpesh V Mehta, "The Most Efficient Waste Heat Recovery Device: A Gamma Type Stirling Engine", International Journal of Advanced Engineering Technology, 2012, 3(1), 189-195.
- 17. M. Dubey, A. Arora, H. Chandra, "Review on Waste Energy Recovery Systems", International Journal of Innovative Research in Science, Engineering and Technology, 2014, 3(12), 18356-18367.
- 18. R. Saidur A, M.Rezaei A, W.K.Muzammil A, M.H. Hassan A, S.Paria A, M. Hasanuzzaman, "Technologies To Recover Exhaust Heat From Internal Combustion Engines", Renewable and Sustainable Energy Reviews, 2012, 16, 5649-5659.
- 19. Marcin Job, Lukasz Bartela, Anna Skorek-Osikowska, "Analysis of the Use of Waste Heat in an Oxy-Combustion Power Plant to Replace Steam Cycle Heat Regeneration", Journal Of Power Technologies, 2013, 93 (3),133-141.
- Pavel Kic, Milan Zajicek, "CFD Model of Regenerative Heat Exchanger", Agric. Eng Int. CIGR Journal, Special Issue 2015, 80-93.

- 21. Daniel Albert, "Design of Heat Recovery System in An aluminum Cast House", Diploma Thesis, Norwegian University Of Science And Technology,2012, Supervisor: Trygve Magne Eikevik, EPT,1-87.
- 22. J. S. Jadhao, D. G. Thombare, "Review on Exhaust Gas Heat Recovery for I.C. Engine", International Journal of Engineering and Innovative Technology (IJEIT), 2013, 2(12), 93-100.
- 23. Nirmal Sajan, Ruben Philip, Vinayak Suresh, Vishnu M, Vinay Mathew John, "Flue Gas Low Temperature Heat Recovery System For Air-Conditioning", International Journal Of Research In Engineering And Technology, 4(4), 71-79.
- 24. Derivusz Mikielewicz, Jan Wajs, Michal Glinski, Jaraslove Mikielewicz, Recovery Of Waste Heat From Coal Fired Power Unil Orgtanic Rankine Using Cycle, Polytechnica Gedanensis, The Results Presented In This Paper Were Obtained From Research Work Co-Financed By The National Centre Of Research Development In The Framework Contract SP/E/1/67484 Strategic Research Program-Advanced Technologies Obtaining Energy: Development Of A Technology For Highly Efficient Zero-Emission Coal-Fired Power /10-Units Integrated With CO₂ Capture.
- 25. S.N. Srinivasa, Dhaya Prasad, N. Parameshwari, "A Feasibility Study On Waste Heat Recovery In An IC Engine Using Electro Turbo Generation", Proceedings Of The National Conference On Trends And Advances In Mechanical Engineering, YMCA University Of Science & Technology, Faridabad Haryana, Oct 19-20, 2012.

How to cite this article: Kulkarni SJ. An overview of studies and research on waste heat recovery with emphasis on hot gases. Int J Res Rev. 2016; 3(8):14-17.
